



Product Service

CERTIFICATE

No. B 134912 0001 Rev. 00

Holder of Certificate: **STEINCO Paul vom Stein GmbH**

Albert-Einstein-Str. 4
42929 Wermelskirchen
GERMANY

Certification Mark:



Product:

**General Medical Devices
Hospital bed castors**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713372061

Valid until: 2030-12-02

Date, 2025-12-03

(Michael Steinmann)

CERTIFICATE

No. B 134912 0001 Rev. 00

Model(s): SERIES568; SERIES569; SERIES560
 SERIES558; SERIES559; SERIES550
 SERIES898; SERIES899; SERIES890
 SERIES878; SERIES879; SERIES870

Brand Name: STEINCO



Parameters:

SERIES568; SERIES569; SERIES560			
Wheel Ø [mm]	100	125	150
Load Capacity dynamic [kg]	150	160	160
Mounting height [mm]	105	130	155
Offset [mm]	33	43	52
Swivel radius [mm]	89	110	131
Wheel width [mm]	16	20	20
Wheel hardness [shore A]	94		
Fitting dimension [mm]	Ø28x95		
Fitting dimension [mm] optional	Ø28x45		
Fitting dimension [mm] optional	Ø32x50		
Fitting dimension [mm] optional	Ø32x50–8kt		

Available options:

conductive
 washable (568W / 569W / 560W)
 total lock (568)
 total lock / directional lock (569)
 without locking system (560)

CERTIFICATE

No. B 134912 0001 Rev. 00

SERIES558; SERIES559; SERIES550		
Wheel Ø [mm]	125	150
Load Capacity dynamic [kg]	160	160
Mounting height [mm]	158	180
Offset [mm]	40	52
Swivel radius [mm]	107	131
Wheel width [mm]	20	20
Wheel hardness [shore A]	94	
Fitting dimension [mm]	Ø28x95	
Fitting dimension [mm] optional	Ø28x45	
Fitting dimension [mm] optional	Ø32x50	
Fitting dimension [mm] optional	Ø32x50–8kt	

Available options:

conductive

washable (558W / 559W / 550W)

total lock (558)

total lock / directional lock (559)

without locking system (550)

CERTIFICATE

No. B 134912 0001 Rev. 00

SERIES898; SERIES899; SERIES890			
Wheel Ø [mm]	125	150	200
Load Capacity dynamic [kg]	160	160	160
Mounting height [mm]	165	188	233
Offset [mm]	35	40	60
Swivel radius [mm]	98	115	160
Wheel width [mm]	36	36	36
Wheel hardness [shore A]	94		
Fitting dimension [mm]	Ø28x95		
Fitting dimension [mm] optional	Ø28x45		
Fitting dimension [mm] optional	Ø32x50		
Fitting dimension [mm] optional	Ø32x50–8kt		

Available options:

conductive

washable (898W / 899W / 890W)

total lock (898)

total lock / directional lock (899)

without locking system (890)

CERTIFICATE

No. B 134912 0001 Rev. 00

SERIES878; SERIES879; SERIES870		
Wheel Ø [mm]	125	150
Load Capacity dynamic [kg]	135	135
Mounting height [mm]	165	188
Offset [mm]	35	40
Swivel radius [mm]	98	115
Wheel width [mm]	32	32
Wheel hardness [shore A]	94	
Fitting dimension [mm]	Ø28x95	
Fitting dimension [mm] optional	Ø28x45	
Fitting dimension [mm] optional	Ø32x50	
Fitting dimension [mm] optional	Ø32x50–8kt	

Available options:

conductive

washable (878W / 879W / 870W)

total lock (878)

total lock / directional lock (879)

without locking system (870)

Tested according to: DIN EN 12531:1999